

HIGH PRODUCTIVITY COMPACT MACHINING CENTER
EQUIPPED WITH DUAL PALLET

VC 3600/30



VC 3600/30

The VC 3600/30 is a compact high-productivity compact machining center designed for the automotive and IT industries. It is equipped with a simultaneous operation function where rotary table turns and the all axes are positioned simultaneously when tools are changed. Durability and reliability have been further improved by adopting a more rigid frame and a servo unit. Dual pallet was applied to improve productivity, and a thermal displacement compensation program was applied as standard for precise and fast processing of various parts. In addition, it provides various convenient functions such as EZ work.

CONTENTS

Product Overview

Basic Information

- 04 Basic Structure
- 05 APC(Automatic Pallet Changer)
- 06 Magazine
- 06 Features
- 07 Standard | Optional Specifications
- 08 Peripheral Equipment

Detailed Information

- 09 FANUC i PLUS
- 10 Power | Torque
- 11 External Dimensions
- 13 Table Dimensions
- 14 Machine Specifications

Customer Support Service

- 15 Customer Support and Services
- 15 Global Network



**SERVO-TYPE APC AND ATCAS
STANDARD FEATURES TO
ACHIEVE EVEN HIGHER
PRODUCTIVITY AND
RELIABILITY**



- Servo-driven APC reduces pallet change time by about 30%.
- Servo-driven ATC incorporating 14 tools as standard feature reduces tool change time by up to 11%.

**NEWLY-DESIGNED DIRECT
COUPLED SPINDLE WITH
IMPROVED RIGIDITY AND
PRODUCTIVITY**



- The spindle design has been optimized by reducing acceleration and deceleration times by up to 30% to achieve even higher productivity.
- Adoption of dual contact spindle as standard feature improves heavy duty machining performance.

**SMALL FOOTPRINT,
VARIOUS USER CONVENIENCE
FEATURES**



- 1620mm (63.8 inch) machine width minimizes footprint.
- Auxiliary chip box (optional) effectively filters fine aluminum chips.



BASIC STRUCTURE

The VC 3600/30, a tool taper ISO #30 class dual pallet compact machining is equipped with a highly reliable servo unit and a new frame, and offers superior productivity and reliability.

High-rigidity structure

The machine's structure has been improved and optimized by CAE analysis to enhance rigidity and thereby ensure stable and accurate machining over long periods.

Travel distance

X-axis

520 mm (20.5 inch)

Y-axis

360 mm (14.2 inch)

Z-axis

350 mm (13.8 inch)



AXIS SYSTEM

Environmentally friendly oil lubrication is adopted as standard for all of the axis feed system, and roller-type LM guides are provided to enhance the rigidity.

Rapid traverse rate

X-axis

48 m/min (1889.8 ipm)

Y-axis

48 m/min (1889.8 ipm)

Z-axis

56 m/min (2204.7 ipm)

Roller-type LM guides are provided as a standard feature

A roller-type LM guide is applied to increase the precision of the linear feed system, which is advantageous for high-speed and high-precision machining.



Oil lubrication for all axes is a standard feature

Grease lubrication system

The standard grease lubrication system eliminates the need for an oil skimmer and reduces lubrication costs by about 60% compared to oil lubrication.

Yearly maintenance cost

Max. **60%** ↓



APC (AUTOMATIC PALLET CHANGER)

The servo driven system has been adopted to further reduce non cutting time (pallet change time), thereby enhancing productivity and reliability.

Variable control of work piece load

Issuing an M-code corresponding to the work weight can change pallets at a speed appropriate for the weight.

Table size

2-650 x 375 mm
(2-25.6 x 14.8 inch)

Max. load capacity

2-200 kg (2-441 lb)

Pallet change time

3 SEC (120 kg on 1 pallet)

Max. work piece height

300 mm (11.8 inch)



SPINDLE

The newly designed direct-coupled spindle offers enhanced productivity and precision with reduced acceleration / deceleration times and lower vibration / noise.

Max. spindle speed

12000 r/min

18000 r/min OPTION



MAGAZINE

Machine reliability has been optimized with the new servo tool magazine, while productivity has been enhanced by reducing the tool change time.

Tool storage capacity

14 ea

21/24 ea OPTION

Tool to Tool

1.6 sec.


Chip to Chip

2.6 sec.

* The Chip-to-Chip time was tested in accordance with DN Solutions's strict testing conditions, but may vary depending on the user's operating conditions.


Simultaneous operation

The Simultaneous Operation Control performs pallet change, and axes home position return and tool change simultaneously to minimize non cutting time.



FEATURES

What's by applying a double chip screw in the machine, the chip disposal ability was improved. And by placing the control panel on the side, operation is easy and safe.



STANDARD | OPTIONAL SPECIFICATIONS

A range of options is available to suit individual requirements.

Description	Features	VC 3600/30	
Spindle	12000 r/min, 13 kW (17.4 Hp), 82.7 N·m (61.0 lbf-ft)	<input type="checkbox"/>	
	18000 r/min, 3.7 kW (5.0 Hp), 11.8 N·m (87.0 lbf-ft)	<input type="checkbox"/>	
Magazine	Tool storage capacity	14 ea	<input type="checkbox"/>
		21 ea	<input type="checkbox"/>
Tool shank type	BIG PLUS ISO #30	<input type="checkbox"/>	
Coolant	FLOOD	0.16 Mpa (24.7 psi), 0.4 kW (0.5 Hp)	<input type="checkbox"/>
	TSC	None	<input type="checkbox"/>
		2 Mpa (290.1 psi), 1.5 kW (2.0 Hp)	<input type="checkbox"/>
	Water soluble Coolant Chiller**		<input type="checkbox"/>
	TOP FLUSHING	0.15 Mpa (1.1 kW)	<input type="checkbox"/>
	Oil skimmer (belt type)		<input type="checkbox"/>
	Coolant level switch : Sensing level - Low / High		<input type="checkbox"/>
Chip disposal	Chip conveyor	Chip pan	<input type="checkbox"/>
		Hinged type (Rear)	<input type="checkbox"/>
		Magnetic scraper type (Rear)	<input type="checkbox"/>
	Chip bucket		<input type="checkbox"/>
	Air blower		<input type="checkbox"/>
	Air gun		<input type="checkbox"/>
	Coolant gun		<input type="checkbox"/>
	Mist collector		<input type="checkbox"/>
Precision machining option	AICC I (40 block)		<input type="checkbox"/>
	AICC II (200 block)		<input type="checkbox"/>
Measurement & Automation	Automatic tool measurement	TS27R_RENISHAW	<input type="checkbox"/>
		NC4_RENISHAW	<input type="checkbox"/>
	Automatic tool breackage detection	NEEDLE SWING TYPE	<input type="checkbox"/>
		OMRON LIMIT SWITCH TYPE	<input type="checkbox"/>
	Automatic workpiece measurement	OMP40_RENISHAW	<input type="checkbox"/>
Automatic front door with safty edge		<input type="checkbox"/>	
Others	Top Cover		<input type="checkbox"/>
	LCD size	10.4 inch	<input type="checkbox"/>
	Signal tower	without Buzzer	<input type="checkbox"/>
		with Buzzer	<input type="checkbox"/>
	Fixture Interface (for each pallet)	Hydraulic (A/B LINE_1 PAIR)	<input type="checkbox"/>
		Pneumatic (A LINE_1 PAIR)	<input type="checkbox"/>
	Hydraulic unit (for hydraulic fixture, 2.2 kW(3.0 hp)		<input type="checkbox"/>
	Automatic power off		<input type="checkbox"/>
SMART THERMAL CONTROL	SENSORLESS TYPE (12k Standard)		<input type="checkbox"/>
	SENSOR TYPE (18k Standard)		<input type="checkbox"/>
Customized Special Option	DRUM CHIPCONVEYOR		<input type="checkbox"/>
	TOOL WASHING		<input type="checkbox"/>

* When using a semi-synthetic type or synthetic type, contact our sales representative or service center in advance.

** Technical consultation is mandatory for the chilling of non-water soluble coolant

* Please contact your DN Solutions representative for detailed machine information.

● Standard ○ Optional X N/A




**Fire Safety
Precautions**

There is a high risk of fire when using non-water-soluble cutting fluids, processing flammable materials, neglecting the controlled and careful use of coolants and modifying the machine without the consent of the manufacturer. Always check the SAFETY GUIDELINES carefully before using the machine.

PERIPHERAL EQUIPMENT

Hydraulic/Pneumatic fixtureline OPTION

Users who intend preparing equipment for hydraulic / pneumatic fixtures should consult DN Solutions to determine correct specification.




TSC OPTION

The through-spindle coolant (TSC) system delivers higher machining efficiency (optional).



An auxiliary chip box

An auxiliary chip box for effective filtering of fine aluminum chips is available as an optional feature




Top cover

The top cover (standard feature) prevents coolant splash, thereby maintaining a clean working environment.



Chip conveyor OPTION



Long

Short

Needle

Sludge

Hinged belt type*

Most common type of chip conveyor. Appropriate for steel materials generating chips over 30mm.

Drum filter type**

Chip conveyor with a magnet: Appropriate for machining cast iron and the generation of fine chips.

Chip conveyor type	Material	Carbon steel			Cast iron		Aluminium		
		Long	Short	Needle	Short	Sludge	Long	Short	Needle
Hinged belt type		○	△	X	△	X	○	△	X
Scraper type	General type	X	○	△	○	△	X	△	X
	Magnetic type	X	○	○	○	○	-	-	-
Drum filter type	Hinged type	○	△	X	△	X	○	△	X
	Scraper type	X	○	△	○	△	X	○	△

○: Suitable, △: Possible, X: Not suitable

Automatic tool Length measurement device OPTION

The Automatic Tool Length Measurement Device monitors excessive tool wear or breakage, and can be used for automatic tool setting.



FANUC i PLUS

DN Solutions FANUC i Plus maximizes customer productivity and convenience.

10.4" Screen + New OP

DN Solutions FANUC i Plus' operation panel enhances operating convenience by incorporating common-design buttons and layout. It features a Qwerty keyboard for fast and easy data input and operation.

FANUC i Plus

- 10.4 inch color display
- Intuitive and user-friendly design

USB and PCMCIA card QWERTY keyboard

- EZ-Guide i standard
- Ergonomic operator panel
- 2MB Memory
- Hot keys



PCMCIA Card

The PCMCIA card enables uploading and downloading of the NC program, NC parameters, tool information, ladder programs, and also supports DNC operation.

USB Port

The USB memory stick enables uploading and downloading of the NC program, NC parameters, tool information and ladder programs. (DNC operation is not supported.)



NUMERIC CONTROL SPECIFICATIONS



Division	Specifications	VC3600/30 FANUC i Plus
Controlled axes		3 (X,Y,Z)
Simultaneously controlled axes		4 axes
Additional controlled Axis	Add 1 Axis (5th Axis)	●
Fast data server		○
Memory card input/output		●
USB memory input/output		●
Large capacity memory(2GB)*2	Note *2) Available Option only with 15" Touch LCD (iHMI Only)	○
Embedded Ethernet		●
Fast Ethernet		○
Enhanced Embedded Ethernet function		●
DNC operation	Included in RS232C interface.	●
DNC operation with memory card		●
Workpiece coordinate system	G52 - G59	●
Addition of workpiece coordinate system	G54.1 P1 X 48 (48 pairs)	○
Tool number command		T2 digits
Tilted working plane indexing command	G68.2 TWP	○
AI contour control I	G5.1 Q_, 40 Blocks	X
AI contour control II	G5.1 Q_, 200 Blocks	●
AI contour control III	G5.1 Q_, 600 Blocks	○
AI contour control IV	G5.1 Q_, 1000 Blocks	X
High smooth TCP		X
EZ Guidei (Conversational Programming Solution)		○
iHMI with Machining Cycle	Note *1) Only with 15" Touch LCD standard	X
EZ Operation package		●
CNC screen dual display function		●
FANUC MTConnect		☆
FANUC OPC UA		☆
Display unit	10.4" color LCD	●
	15" color LCD	X
	15" color LCD with Touch Panel	X
	640M(256KB)_500 programs	X
Part program storage size & Number of registerable programs	1280M(512KB)_1000 programs	X
	2560M(1MB)_1000 programs	X
	5120M(2MB)_1000 programs	●
	10240M(4MB)_1000 programs	X
	20480M(8MB)_1000 programs	X
	2560M(1MB)_2000 programs	X
	5120M(2MB)_4000 programs	X
	10240M(4MB)_4000 programs	X
	20480M(8MB)_4000 programs	X

* Fanuc i plus iHMI available.

● Standard ○ Optional X/N/A ☆ Available

POWER | TORQUE

DN Solutions FANUC i

Max. spindle speed


12000 r/min

Max. spindle motor power

13 kW
(17.4 Hp)

Max. spindle motor torque

82.7 N·m
(61.0 lbf-ft)



DN Solutions FANUC i OPTION

Max. spindle speed


18000 r/min

Max. spindle motor power

3.7 kW
(5.0 Hp)

Max. spindle motor torque

11.8 N·m
(8.7 lbf-ft)




EXTERNAL DIMENSIONS


ARMLESS TYPE

Unit : mm (inch)


FRONT



SIDE



SIDE




* Some peripheral equipment can be placed in other areas.

EXTERNAL DIMENSIONS


CAM TYPE

Unit : mm (inch)

FRONT



SIDE



SIDE






TABLE DIMENSIONS

Unit : mm (inch)

T-SLOT



TAP HOLE



MACHINE SPECIFICATIONS

Description		Unit	VC 3600/30	
Travels	Travel distance	X axis	mm (inch)	520 (20.5)
		Y axis	mm (inch)	360 (14.2)
		Z axis	mm (inch)	350 (13.8)
	Distance from spindle nose to table top		mm (inch)	150 ~ 500 (5.9 ~ 19.7)
Table	Table size		mm (inch)	2-650 x 375 (2-25.6 x 14.8)
	Table loading capacity		kg (lb)	2-200 (2-441)
	Table surface type		mm (inch)	TAP HOLE TYPE 2X32(0.1X1.3)-M12(0.5)XP1.75(0.1) {T-SLOT TYPE 2X3-100X14H8 (0.1X0.1-3.9X0.6H0.3) } *
Spindle	Max. spindle speed		r/min	12000 {18000}*
	Taper		-	ISO #30
	Spindle power		kW (Hp)	13(17.4){S3 15%}/3.7(5.0)(cont.) {3.7(5.0){S2 5min}/1.1(1.5)(cont.)}*
	Max. spindle torque		N·m (lbf·ft)	82.7(61.0) {11.8(8.7)}*
Feedrates	Rapid traverse rate	X axis	m/min (ipm)	48 (1889.8)
		Y axis	m/min (ipm)	48 (1889.8)
		Z axis	m/min (ipm)	56 (2204.7)
Automatic Tool Changer	Type of tool shank	Tool shank	-	BT 30
		Pull stud	-	MAS403 P30T-1 45deg.
	Tool storage capa.		ea	14{21}* (Armless type) / 24(Cam type)
	Max. tool diameter	Continuous	mm (inch)	80(Armless type) / 60(Cam type)
		Without Adjacent Tools	mm (inch)	150(Armless type) / 130(Cam type)
	Max. tool length		mm (inch)	200 (7.9)
	Max. tool weight		kg (lb)	2.8 (6.2)
	Max. tool moment		N·m (lbf·ft)	1.47 (1.1)
	Tool selection			FIXED ADDRESS
	Tool change time	Tool-to-tool	sec	1.6(Armless type) / 1.1(Cam type)
Chip-to-chip		sec	2.6(Armless type) / 2.8(Cam type)	
Power source	Electric power supply (rated capacity)		kVA	FANUC-19.8 {16.5}
	Compressed air supply		MPa (psi)	0.54 (78.3)
Tank capacity	Coolant tank capacity		L (gal)	300 (79.3)
Machine Dimensions	Height		mm (inch)	2552 (100.5) {2657(80.3)}
	Length		mm (inch)	3630 (142.9)
	Width		mm (inch)	1740 (68.5)
	Weight		kg (lb)	5200 (11463.9)
Control	CNC system		-	DN Solutions Fanuc i Plus

RESPONDING TO CUSTOMERS **ANYTIME, ANYWHERE**

DN SOLUTIONS GLOBAL NETWORK

66 COUNTRIES | **140** + SALES NETWORKS | **3** FACTORIES | **6** REGIONAL HQS



CUSTOMER SUPPORT AND SERVICES

WE'RE THERE FOR YOU WHENEVER YOU NEED US.

We help our customers operate at maximum efficiency by providing them with a range of tried, tested and trusted services - from pre-sales consultancy to post-sales support.

	<p>FIELD SERVICES</p> <ul style="list-style-type: none"> • On-site service • Machine installation and testing • Scheduled preventive maintenance • Machine repair service 		<p>PARTS SUPPLY</p> <ul style="list-style-type: none"> • Supplying a wide range of original DN Solutions spare parts • Parts repair service
	<p>TRAINING</p> <ul style="list-style-type: none"> • Programming, machine setup and operation • Electrical and mechanical maintenance • Applications engineering 		<p>TECHNICAL SUPPORT</p> <ul style="list-style-type: none"> • Supports machining methods and technology • Responds to technical queries • Provides technical consultancy



Head Office

19F, 10, Tongil-ro, Jung-gu, Seoul,
Republic of Korea, 04527

Tel: +82-2-6972-0370
Fax: +82-2-6972-0400

DN Solutions America

360 E State PKWY,
Schaumburg, IL. 60173,
United states

Tel: +1-315-265-7500

DN Solutions Europe

Emdener Strasse 24, D-41540
Dormagen, Germany

Tel: +49-2133-5067-100
Fax: +49-2133-5067-111

DN Solutions India

No.82, Jakkuar Village
Yelahanka Hobil,
Bangalore-560064

Tel: +91-80-2205-6900
E-mail: india@dncompany.com

DN Solutions China

Room 101,201,301,
Building 39 Xinzhuan Highway
No.258 Songjiang District
China Shanghai (201612)

Tel: +86 21-5445-1155
Fax: +86 21-6405-1472

DN Solutions Vietnam

M.O.R.E building 2F, 40A-40B Ut
Tich Street, 04 Ward 04,
District Tan Binh District,
Ho Chi Minh City, Vietnam

Tel: +84 28-7304-0163

DN Solutions Mexico

Avenida Parque Bicentenario
#100 Nave M65L3-6,
Fraccionamiento San Isidro
Business Park,
Santa Rosa Jauregui,
Querétaro, México

E-mail: efrain.figueroa@dncompany.com

Sales inquiry

sales@dncompany.com